

Personnel Badge Lite

What does it do?

This wearable badge combines three functions into a single device:

- Location Tracking The badge reports its location up to four times per second, allowing you to track users in real-time with high accuracy.
- **Communication** The call button let the user receive and acknowledge warning.
- PWS Support No network infrastructure needed. Visual, audio and haptic alarm between vehicles and vehicles, vehicles and people, vehicles and infrastructure.

How can you use it?

Location Tracking

- You can quickly ensure users are in their designated areas or monitor users who may be in hazardous areas.
- You can capture historical location data for all users to provide precise time and location accountability.

Safety

 Badge sends alarms with flashing LED lights, audible notifications and haptic feedback to alert users when they are entering a dangerous area or being approached by a fast-moving vehicle.

Communication

• Users can press the emergency call button for help.

Key Features

Accurate Accurate up to 10 cm.

Responsive

200ms latency is essential for safety applications where a fraction of a second makes a difference.

Informative

A flashing LED, audible beep and haptic feedback notify the wearer of safety alerts.

Interactive

A call button lets the user acknowledge alarms and alerts or call for help.



Personnel Badge Lite Front

Redpoint Positioning Corp.

Product Fact Sheet



| | Value |
|------------------------|--------------------------------------|
| Operating Frequency | 3.2 - 6.7 GHz |
| Battery Type | Single-cell lithium-ion rechargeable |
| Battery Life Active | 12 hours |
| Battery Life Idle | 30 hours |
| Battery Charge Current | 500 mA |
| Battery Charge Time | 3 hours |

Peripherals

| Parameter | Value |
|---------------|--|
| Call Button | Sends message to the server. Multi-functional, including sending an emergency message. |
| Visual Alert | RGB LED provides status as well as user-alert functionality |
| Haptic Alert | Haptic alerts for safety hazards and incoming messages |
| Audible Alert | On-board buzzer alerts for safety hazards and incoming messages |
| Motion | 6-axis IMU for motion sensing and power management |
| Bluetooth | Support Bluetooth Low Energy (BLE) communication |

Mechanical & Environmental

| Parameter | Value |
|-----------------------|-------------------|
| Dimension | 62 x 98 x 10 (mm) |
| Weight | 54 g |
| Operating Temperature | -20°C to 50°C |
| Charging Temperature | 5°C to 40°C |
| IP Rating | In process |

Accessories

| Parameter | Value |
|------------------|--------------------------------------|
| Charging | Standard USB-C cable or bank charger |
| Charging Voltage | 5V |

Ordering information

The badge and accessories may be ordered directly through Redpoint. Please place a request using part number 9000-0716 for the Personnel Badge Lite.

Redpoint Positioning Corp.

100 N Washington St, 6th floor, Boston, MA 02114 | +1 (617) 207-4096 Send inquiries to info@redpointpositioning.com or visit our website at www.redpointpositioning.com

Personnel Badge Lite Back



Personnel Badge Lite Side

